



Tyre Shine (Silicone Solvent)

Product Data Sheet

Use - Automotive Application
Tyre Shine (Solvent Based Silicone Product)

TYPICAL PROPERTIES

Appearance:	Clear Colourless Liquid
Odour:	Petroleum Odour
pH:	Not applicable
Density:	0.72—0.75
Flammable:	Highly Flammable
Melting Point:	Not available
Boiling Point:	—120°C
Solubility:	Insoluble
Flash Point:	< -15°C

This product is considered hazardous according to the criteria of Workplace Australia.

PRODUCT INFORMATION

PTS is a high quality silicone tyre treatment. PTS is formulated with silicones that provide a consistent, shiny finish when applied correctly. Rejuvenates tyres and aged vinyl. Resists water and outlasts most competitive products. PTS is economical and efficient to use.

APPLICATION

May be sprayed, painted or wiped onto surfaces. Best results are achieved by spraying surface evenly and allowing 15 minutes to dry. Should faster drying be necessary wiping with a clean rag after spraying may be necessary. This may leave a slightly less shiny finish. Austech 1 Litre Pump-up Sprays are recommended for this application.

PRECAUTIONS

This product is highly flammable and should be treated accordingly. Product MSDS should be read before using.

SUMMARY

PTS is an extremely versatile vinyl rejuvenator and protector, ideal for use in external situations.

PRODUCT CODES / QUANTITIES

A/PTS/5	5L Plastic Jerry Can (Box of 4)
A/PTS/20	20L Plastic Drum
A/PTS/200	200L Metal Drum