



Truck Wash

Product Data Sheet

Use - Automotive Application
Truck Wash

TYPICAL PROPERTIES

Appearance:	Light Blue Liquid
Odour:	Slight Odour
pH:	(5% solution) 8.68
Flammable:	Non flammable
Melting Point:	-4°C
Boiling Point:	121°C
Solubility:	Soluble
Flash Point:	Not applicable
Specific Gravity:	1.075

PRODUCT INFORMATION

PTW is a concentrated water based truck wash. This product effectively removes road grime and dirt from all surfaces including plastic, rubber, chrome, aluminium and paintwork. PTW is bio-degradable and free rinsing.

APPLICATION

PTW is primarily used to wash trucks, cars, boats, coaches etc.

PTW is also an effective floor cleaner and laundry cleaner (especially on greasy clothing).

BENEFITS

Contains corrosion inhibitors to protect surface from rusting.

Leaves paintwork shiny and streak free when used accordingly.

This product is economical to use.

DIRECTIONS FOR USE

1. Dilute PTW with water to the required strength. Dilution rate for vehicle washing is 1 part PTW with 50 parts water. Prepare stronger solutions for cleaning heavily soiled items.
 2. Apply AC49 solution to the surfaces to be cleaned using a sponge or spray. Scrub heavily soiled surfaces to remove excess dirt.
 3. Allow several minutes for PTW to penetrate the grime then thoroughly rinse with water hose. For best results, wash surfaces out of direct sunlight.
-

PRODUCT CODES / QUANTITIES

A/PTW/20	20L Plastic Drum
A/PTW/200	200L Metal Drum